

SPECIFICATIONS

- **MATERIAL/FEATURES**
 - 304 Stainless Steel Case
 - ETL Approved to UL1838
 - Bottom Panel pre-punched with conduit knockouts, and swings down for ease of installation and is fully removable
 - Quick Mount Bracket Allows for mounting without templates
 - Lifetime Warranty
 - Sealed removable, lockable hinged doors
- **FINISH**
 - Muted Stainless Steel
- **ELECTRICAL**
 - 6' Heavy Duty Power Cord
 - Large terminal blocks allow for 10 #12/2 or 8 #10/2 wire
 - Primary Side Thermal Protection
 - Secondary Side Magnetic Circuit Breakers
 - *Fully Encapsulated EI Magnetic Core*
 - Surge Suppressor provides protection against initial start overload on primary circuits
 - Internal wiring rated to 125°C
 - 115 AMP rated terminal block
 - Primary AMP loop provided on 900 & 1200 watt models
- **DIMENSIONS**
 - 300, 600 watt - 6 1/5" W x 16 1/2" H x 6" D
 - 900, 1200 watt - 8 1/2" W x 17 1/2" H x 7" D
- **MODELS**
 - MTM0300SS 300w 12,13,14,15 volt taps
 - MTM0600SS 600w 12,13,14,15 volt taps
 - MTM0900SS 900w 12,13,14,15 volt taps
 - MTM1200SS 1200w 12,13,14,15 volt taps
- **OPTIONS - sold separately**
 - PC - Transformer mount photocell
 - MT1 - Mechanical Timer - 48 ON/OFF positions
 - MT2 - Mechanical Timer - 7 Day Programmable
 - DT - Digital Timer - 7 day Programmable



SPECIFICATIONS



- **MATERIAL/FEATURES**
 - 304 Stainless Steel Case
 - ETL Approved to UL1838
 - Bottom Panel pre-punched with conduit knockouts, and swings down for ease of installation and is fully removable
 - Quick Mount Bracket Allows for mounting without templates
 - Lifetime Warranty
 - Sealed removable, lockable hinged doors
- **FINISH**
 - Muted Stainless Steel
- **ELECTRICAL**
 - 6' Heavy Duty Power Cord
 - Large terminal blocks allow for 10 #12/2 or 8 #10/2 wire
 - Primary Side Thermal Protection
 - Secondary Side Magnetic Circuit Breakers
 - *Fully Encapsulated Toroid Core*
 - Surge Suppressor provides protection against initial start overload on primary circuits
 - Internal wiring rated to 125°C
 - 115 AMP rated terminal block
 - Primary AMP loop provided on 900 & 1200 watt models
- **DIMENSIONS**
 - 300, 600 watt - 6 1/5" W x 16 1/2" H x 6" D
- **MODELS**
 - MTT0300SS 300w 12,13,14,15 volt taps
 - MTT0600SS 600w 12,13,14,15 volt taps
- **OPTIONS - sold separately**
 - PC - Transformer mount photocell
 - MT1 - Mechanical Timer - 48 ON/OFF positions
 - MT2 - Mechanical Timer - 7 Day Programmable
 - DT - Digital Timer - 7 day Programmable



SPECIFICATIONS

- **MATERIAL/FEATURES**
 - 304 Stainless Steel Case
 - ETL Approved to UL2108
 - Bottom Panel pre-punched with conduit knockouts, and swings down for ease of installation and is fully removable
 - Quick Mount Bracket Allows for mounting without templates
 - Lifetime Warranty
 - Sealed removable, lockable hinged doors
- **FINISH**
 - Muted Stainless Steel
- **ELECTRICAL**
 - 6' Heavy Duty Power Cord
 - Large terminal blocks allow for 10 #12/2 or 8 #10/2 wire
 - Primary Side Thermal Protection
 - Secondary Side Magnetic Circuit Breakers
 - *Fully Encapsulated Toroid Core*
 - Surge Suppressor provides protection against initial start overload on primary circuits
 - Internal wiring rated to 125°C
 - 115 AMP rated terminal block
 - Primary AMP loop provided on 900 & 1200 watt models
- **DIMENSIONS**
 - 300, 600 watt - 6 1/5" W x 16 1/2" H x 6" D
 - 900, 1200 watt - 8 1/2" W x 17 1/2" H x 7" D
- **MODELS**
 - MTP0300SS 300w 12,13,14,15,16,17,18,22v
 - MTP0600SS 600w 12,13,14,15,16,17,18,22v
 - MTP0900SS 900w 12,13,14,15,16,17,18,20,22v
 - MTP1200SS 1200w 12,13,14,15,16,17,18,20,22v
- **OPTIONS - sold separately**
 - PC - Transformer mount photocell
 - MT1 - Mechanical Timer - 48 ON/OFF positions
 - MT2 - Mechanical Timer - 7 Day Programmable
 - DT - Digital Timer - 7 day Programmable



SPECIFICATIONS



- **MATERIAL/FEATURES**
 - 304 Stainless Steel Case
 - ETL Approved to UL1838
 - Bottom Panel pre-punched with conduit knockouts, and swings down for ease of installation and is fully removable
 - Quick Mount Bracket Allows for mounting without templates
 - Lifetime Warranty
 - Removable lockable door
 - Manual On/Off only, controlled at receptacle
- **FINISH**
 - Muted Stainless Steel
- **ELECTRICAL**
 - 6' Heavy Duty Power Cord
 - Large terminal blocks allow for 10 #12/2 or 8 #10/2 wire
 - Primary Side Thermal Protection
 - Secondary Side Magnetic Circuit Breakers
 - *Fully Encapsulated EI Magnetic Core*
 - Surge Suppressor provides protection against initial start overload on primary circuits
 - Internal wiring rated to 125°C
 - 115 AMP rated terminal block
- **DIMENSIONS**
 - 300 watt - 6 1/2" W x 11 1/2" H x 5 1/2" D
 - 600 watt - 6 1/4" W x 11 1/2" H x 5 1/2" D
 - 900 watt - 5 1/4" W x 11 1/2" H x 5 1/2" D
- **MODELS**

• MTC0300SS	300w	12,13,14,15 volt taps
• MTC0600SS	600w	12,13,14,15 volt taps
• MTC0900SS	900w	12,13,14,15 volt taps

SPECIFICATIONS

- **MATERIAL/FEATURES**
 - 304 Stainless Steel Case
 - ETL Approved to UL1838
 - Side Panel pre-punched with conduit knockouts
 - Quick Mount Bracket Allows for mounting without templates
 - Lifetime Warranty
 - Manual On/Off only, controlled at receptacle
- **FINISH**
 - Muted Stainless Steel
- **ELECTRICAL**
 - 6' Heavy Duty Power Cord
 - Hard Wire Connections required
 - Primary Side Thermal Protection
 - Secondary Side Magnetic Circuit Breakers
 - *Fully Encapsulated EI Magnetic Core*
 - Surge Suppressor provides protection against initial start overload on primary circuits
 - Internal wiring rated to 125°C
- **DIMENSIONS**
 - 150 watt - 4" W x 7" H x 3 1/4" D
 - 300 watt - 5 1/4" W x 9" H x 4 1/2" D
 - 600 watt - 5 1/4" W x 9" H x 4 1/4" D
- **MODELS**

• MTE0150SS	150w	12,13,14,15 volt wires
• MTE0300SS	300w	12,13,14,15 volt wires
• MTE0600SS	600w	12,13,14,15 volt wires

