

SPECIFICATIONS

- MATERIAL/FEATURES**
 - Aluminum or Brass
 - Louvered or Frosted Lens Covers
 - Half Size
 - Full Size
 - *Recessed Box Sold Separately (see page 20)*
- FINISH**
 - Weather Resistant Powder Coat Finish - Aluminum
 - Weather Resistant Chemical Finish - Brass
 - Brass finishes will vary over time, and are warranted not to corrode
- DIMENSIONS**
 - 4 1/2" W x 2 7/8" H x 5/8" D - Half Size
 - 8 3/4" W x 2 7/8" H x 5/8" D - Full Size
- MODELS**
 - Aluminum

	<u>Full Size (fits SLB8100BK box)</u>		
<i>Louvered</i> -	SLC1100AB	SLC1100AS	SLC1100AZ
<i>Frosted</i> -	SLC1101AB	SLC1101AS	SLC1101AZ
	<u>Half Size (fits SLB8110BK box)</u>		
<i>Louvered</i> -	SLC1110AB	SLC1110AS	SLC1110AZ
<i>Frosted</i> -	SLC1111AB	SLC1111AS	SLC1111AZ
 - Brass

	<u>Full Size (fits SLB8100BK box)</u>	
<i>Louvered</i> -	SLC2100WB	SLC2100CF
<i>Frosted</i> -	SLC2101WB	SLC2101CF
	<u>Half Size (fits SLB8110BK box)</u>	
<i>Louvered</i> -	SLC2110WB	SLC2110CF
<i>Frosted</i> -	SLC2111WB	
- APPLICATIONS**
 - Entry Columns
 - Stairs/Steps Decking



SLC2100WB shown



SLC2110BS shown
special order color BS



SLC1101AS shown



SLC2111SC shown
special order color SC



SPECIFICATIONS



SLB8100BK



SLB8110BK



- **MATERIAL/FEATURES**
 - High temperature polymer, corrosion resistant box
 - Full reflector for maximum light output
 - Half Size
 - Full Size
 - *Covers sold seperately (see page 19)*
- **ELECTRICAL**
 - 3' - #18/2 Direct Bury Landscape Lighting Wire
 - Optional - 25' - #16/2 Direct Bury Landscape Lighting Wire
- **LAMP**
 - Hi-temp ceramic socket w/stainless steel spring
 - Includes 12 Volt T3 20 watt XENON Bi-pin Bulb
 - Maximum 20 watt
- **LED - OPTIONAL**
 - 5 Watt white (4,000k) LED - SLB8100BK-5LED
 - 3 Watt white (4,000k) LED - SLB8110BK-3LED
 - LED operating range 10v - 22v
- **DIMENSIONS**
 - 4 9/16" W x 2 1/2" H x 3" D
 - 8 5/8" W x 2 1/2" H x 3" D
- **MODELS**
 - Polymer
 - SLB8100BK - Full Size
(fits SLC1100xx, SLC1101xx, SLC2100xx, SLC2101xx)
 - SLB8110BK - Half Size
(fits SLC1110xx, SLC1111xx, SLC2110xx, SLC2111xx)
- **OPTIONS**
 - LED - add -5LED to end of model #SLB8100BK-5LED
 - 25' 16/2 Wire Leads add -25 to end of model # SLB8110BK-25
- **APPLICATIONS**
 - Entry Columns
 - Stairs/Steps Decking
- **AREA**
 - SLB8100BK - Illuminates an area from 8' to 15'
 - SLB8110BK - Illuminates an area from 4' to 10'
- **SPACING**
 - SLB8100BK - suggested spacing from 10' to 20'
 - SLB8110BK - suggested spacing from 6' to 12'

