

LED – LX1

LX1-G4, S8, BA15S

SPECIFICATIONS

- Silica Gel Lamps – IP67 Rated
- G4 Socket Base – T3 Bi Pin
- 80+ CRI
- 90+CRI14
- 40,000 Hour rated
- LED's are measured and tested @ 12 Volts
 - Longest Life occurs at 12 Volts
- Stainless Steel Pins
- Silver Soldering for Long Lasting Performance
- Made for use in Enclosed Fixtures and Damp Location
- 2700K and 3000K Color Temperature
- LX1-G4-27K and LX1G4-30K
 - 120 Lumens – 3.25 Watts
- LX1-S8-27K and 30K
 - 120 Lumens – 3.25 Watts
- LX1-BA15S-27K and LX1-BA15S30K
 - 120 Lumens – 3.25 Watts

ELECTRICAL

- 9-15 V AC/DC
- COB Chip On Board LED Chip Technology
- Constant Current Driver Included for Long Life
- Dimmable with Lutron Magnetic Dimmers
 - Dimming may Reduce Life Span
- Enclosed Fixture Required (Not Included)
- Low Voltage Transformer or Electronic Transformer Required (Not Included)
- C ETL Listed and Approved

MODELS

- LX1G4-27K or LX1-G4-30K
- LX1-S8-27K or LX1-S8-30K
- LX1-BA15S-27K or LX1-BA15S30K

