

Area Flood

AF1300

MATERIAL / FIXTURES

- Heavy Duty Cast Aluminium
- Heat Resistant Interchangeable Gasket and Lenses included
 - Clear Lens
 - Frosted Lens
- Includes (GS1) ABS Ground Stake, 1/2" NPT thread, slotted for ease of installation
- EPDM Rubber Bug Plug, prevents moisture/bugs from entering fixture
- Thumb Screw on knuckle for easy field adjustment
- "O" Ring Seal for added moisture protection
- Weather Resistant Powder Coat Finish - Aluminium
 - (BK) Black – AF1300BK
 - (BZ) Commercial Bronze - AF1300BZ
- Includes two AC-102 silicone filled wire connectors

ELECTRICAL

- 12 Volt Fixture
- 3' - #18/2 Direct Bury Landscape Lighting Wire
- Hi-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required – two options:
- MR16 50 W Max
- T3 35 W Max
- Low Voltage Transformer required (not included)
- Wire connectors included
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps
- LV1-T3
- LV2-T3
- LV3-T3

DIMENSIONS

- AF1300 – 6.75 L x 4" W x 3" H across the front shroud



AF1300BK



LXC2-MR16



LXC3-MR16



LXC5-MR16



LV1-T3



LV2-T3



LV3-T3

