

Directional Spot

DS1300

MATERIAL / FEATURES

- Heavy Duty Cast Aluminum
- Optional Cowling Thumb Set Screw - allowing downlight use
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS Ground Stake, 1/2" NPT thread, slotted for ease of installation
- EPDM Rubber Bug Plug, prevents moisture/bugs from entering fixture
- Thumb Screw on knuckle for easy field adjustment
- Double "O" Ring Seal for added moisture protection
- Weather Resistant Powder Coat Finish - Aluminum
 - (BK) Black - DS1300BK
 - (BZ) Commercial Bronze - DS1300BZ
- Includes two AC-102 silicone filled wire connectors



DS1300BK

ELECTRICAL

- 12 Volt Fixture
- 3' - #18/2 Direct Bury Landscape Lighting Wire
- Hi-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required – MR16 50 W Max
- Low Voltage Transformer required (not included)
- Wire connectors included
- C ETL listed and approved



DS1300BZ

LED LAMP OPTIONS

- LXC MR16 Lamps
 - LXC2, LXC3, LXC5
 - See LED lamp pages

DIMENSIONS

- DS1300 – 6.25" L x 2.5" W



LXC2-MR16



LXC3-MR16



LXC5-MR16

