

Directional Spot

DS2800WB

MATERIAL / FEATURES

- Heavy Duty Cast Brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS Ground Stake, 1/2" NPT thread, slotted for ease of installation
- EPDM Rubber Bug Plug, prevents moisture/bugs from entering fixture
- Thumb Screw on knuckle for easy field adjustment
- Double "O" Ring Seal for added moisture protection
- Weather Resistant Aged Finish - Brass
 - (WB) Weathered Bronze
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors

ELECTRICAL

- 12 Volt fixture
- 3' - #18/2 Direct Bury Landscape Lighting Wire
- Hi-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required – MR16 50W Max
- Low Voltage Transformer required (not included)
- Wire connectors included
- C ETL listed and approved

LED LAMP OPTIONS

- LXC MR16 Lamps
 - LXC2, LXC3, LXC5
 - See LED lamp pages

DIMENSIONS

- DS2800WB – 7.25" L x 2.5" W



DS2800WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

