

# Hybrid Integrated

## Hi-DS\*

### MATERIAL / FEATURES

- Hi-bred Integrated LED directional spotlight
  - The benefits and features of an integrated led fixture
    - Heat Sink for I-LED-MR16-600L module
    - 10 Year Warranty LED module
  - Three Lumen outputs
  - Three Beam Spread options
- Field replaceable LED Module
- External Lumen modulation button
- Adjustable cowling
- Heat resistant angled glass lens
- Includes (GS1) ABS Ground Stake. ½" NPT thread, slotted for ease of installation
- EPDM Rubber Bug Plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle
- Double O-ring seal for added moisture protection
- Weather resistant Heavy-Duty Cast Brass
  - Lifetime warranty – fixture housing
  - WB finish will patina / tarnish depending on environmental conditions
- Weather resistant Cast Aluminum

### ELECTRICAL

- 12 Volt fixture
- 3' - #18/2 Direct Bury landscape Lighting Wire
- Hi-LEDMR16-600 LED Lighting Module (Included)
- Low Voltage Transformer required (not included)
- Wire Connectors required (Not included)
- C ETL listed and approved
- FCC Certified

### LED – LIGHTING MODULE

- Encapsulated thermal plastic LED module
- COB Chipset technology
- Heat Sink for better thermal management
- Three pre-set button guided lumen outputs
  - 300, 400, 600 Lumens
- Three pre-set lighting module beam spread options
  - 15, 38, 60 degrees
- Watts / VA / PF
- Field Replaceable LED Module
  - Hi-LEDMR16-600
  - 10-year warranty
- Models
  - Aluminum: Hi-DS1560BZ or Hi-DS1560BK
  - Brass Hi-DS2560WB
- IP65



HI-DS2560WB

