

Ledge Light

LL4403, LL4407, LL4413

MATERIAL / FEATURES

- Stainless Steel
 - Mounting Bracket
 - Screws
 - Glare Shield
- Cast Aluminium – Light Bar
- Mounting Bracket includes pre-scored corners for retrofit installations (LL4407BZ) only
- LED Light Bar can be used
 - By itself
 - With Glare Shield or without
 - With Bracket or without
- Models:
 - 1 LED – LL4403BZ
 - 4 LED's – LL4407BZ
 - 8 LED'S – LL4413BZ



LL4403BZ

ELECTRICAL

- Input 9-15 Volts
- 10' - #18/2 Dire cape Lighting Wire
- No Lamp required
- LED Diodes have 90° Beam Spread
- Low Voltage Transformer required (not included)
- Wire Connectors required (not included)
- C ETL listed and approved
- FCC Certified



LL4407BZ

LED SPECIFICATIONS

- LED Integrated – No lamp required
- LL4403BZ – 25 Lumens, .4 Watts, VA .60, 366 PF
- LL4407BZ – 100 Lumens, 1.25 Watts, VA 2, .62 PF
- LL4413BZ – 200 Lumens, 2.2 Watts, VA 3.3, .85 PF



LL4413BZ

DIMENSIONS

- LL4403BZ - 3" W x .75" H x 3" D
- LL4407BZ - 7" W x .75" H x 3" D
- LL4413BZ - 13" W x .75" H x 3" D

