

W/L

Wet Location



Wet Location

WL2100WB-25

MATERIAL / FIXTURES

- Heavy Duty Cast Brass
- Heat Resistant Glass Lens
- Easy Lamp Replacement
- Includes Heavy Cast Brass Adjustable Weighted Bracket
- Watertight Sealed Wire Ingress Grommet
- Brass Thumb Screws on bracket for easy field adjustment
- Watertight Sealed Gasket
- Finish
 - Chemically Aged Finish – Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
 - (WB) Weathered Bronze – WL2100WB-25
 - Includes two AC-102 silicone filled wire connectors

ELECTRICAL

- 12 Volt Fixture
- 25' Submersible Rated Lighting Wire Lead
- Hi-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required – MR16 50 W Max
- Low Voltage Transformer required (not included)
- Wire connectors included
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps

DIMENSIONS

- WL2100WB
 - Base - 4.42 D x 5" W
 - Fixture – 3.25" W x 5.25" H



WL2100WB



Intertek



LXC2-MR16



LXC3-MR16



LXC5-MR16

