

Hybrid Integrated

Hi-DS*

MATERIAL / FEATURES

- Hybrid Integrated LED directional spotlight
 - The benefits and features of an integrated led fixture
 - Heat Sink for I-LED-MR16-600L module
 - 10 Year Warranty LED module
 - Three Lumen outputs
 - Three Beam Spread options
 - Field replaceable LED Module
- External Lumen modulation button
- Adjustable cowling
- Heat resistant angled glass lens
- Includes (GS1) ABS Ground Stake. 1/2" NPT thread, slotted for ease of installation
- EPDM Rubber Bug Plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle
- Double O-ring seal for added moisture protection
- Weather resistant Heavy-Duty Cast Brass
 - Lifetime warranty – fixture housing
 - WB finish will patina / tarnish depending on environmental conditions
- Weather resistant Cast Aluminum
- Includes two AC-102 silicone filled wire connectors

ELECTRICAL

- 12 Volt fixture
- 3' - #18/2 Direct Bury landscape Lighting Wire
- Hi-LEDMR16-600 LED Lighting Module (Included)
- Low Voltage Transformer required (not included)
- Wire connectors included
- C ETL listed and approved
- FCC Certified

LED – LIGHTING MODULE

- Encapsulated thermal plastic LED module
- COB Chipset technology
- Heat Sink for better thermal management
- Three pre-set button guided lumen outputs
 - 300, 400, 600 Lumens
- Three pre-set lighting module beam spread options
 - 15, 38, 60 degrees
- 300 Lumens
 - 3W, 4.06 VA, .77 PF
- 400 Lumens
 - 5W, 6.44 VA, .77 PF
- 600 Lumens
 - 7W, 9.00 VA, .77 PF
- Field Replaceable LED Module
 - Hi-LEDMR16-600
 - 10-year warranty
- Models
 - Aluminum: Hi-DS1560BZ or Hi-DS1560BK
 - Brass Hi-DS2560WB
- IP65



HI-DS2560WB

