

ILED-DS2025WB Installation Instructions

SAVE THESE INSTRUCTIONS

WARNING - TO REDUCE THE RISK OF FIRE OR INJURY TO PERSONS

- Turn power OFF or unplug fixture and allow it to cool before removal.
- Luminaire gets HOT quickly. Contact only switch/plug when turning on.
- Do not touch hot lens, guard, or fixture housing until it has cooled.
- Keep luminaire away from combustibles.

IMPORTANT SAFETY INSTRUCTIONS

- For outdoor use only.
- Make sure the power is turned OFF before installing or servicing this fixture.
- WARNING: Risk of electrical shock. Install all fixtures 10 feet (3.05 m) or more from a pool, spa, or fountain.
- This fixture is to be used with a low voltage power supply that does not exceed 15V.
- Position the wire and wire connector so that is connected within 6 inches (15.2 cm) from a building structure, a fixture or fitting.
- Not to be buried except for a maximum of 6 inches to connect to the main low voltage cable.

FIXTURE MOUNTING INSTRUCTIONS

- 1. Disconnect transformer from main power supply.
- 2. Thread the post onto the fixture.
- 3. Thread the lower portion of the post to the GS-Mini ground stake provided.
- 4. Strip the two fixture wires.
- 5. Attach the two fixture wires to the main supply cable leads using waterproof connectors.
- 6. Reconnect the transformer to the primary power supply.



LED-DS2025WB Installation Instructions

