



## LV2-DCB, LV2-SCB

### LED - Bayonet

MATERIAL	MODEL NUMBER	LUMENS	KELVIN
UV protected Clear Silica	LV2-DCB-27K LED	170 Lumens	2700K
UV protected Clear Silica	LV2-DCB-30K LED	170 Lumens	3000K
UV protected Clear Silica	LV2-SCB-27K LED	170 Lumens	2700K
UV protected Clear Silica	LV2-SCB-30K LED	170 Lumens	3000K

### SPECIFICATIONS:

**Material:**

- Solid Silica Gel

**Finish:**

- Clear, UV inhibitor infused to prevent yellowing or caking.

**Socket Type:**

- BA15-S Single contact base.

**Pin gap width:**

- 15 Millimeters

**Dimensions:**

- LV2-DCB: .7" W x 1.65" H
- LV2-SCB: .7" W x 1.65" H

**Voltage Range:**

- 12-15 volts AC/DC

**IP Rating:**

- IP 65
- Made for use in enclosed fixtures.

**Electrical:**

- LV2-DCB: 170 Lumens, 2.5 Watts, .17 VA, .7 PF
- LV2-SCB: 170 Lumens, 2.5 Watts, .17 VA, .7 PF

**Rated Hours:**

- 25,000

**Dimmable:**

- Yes with secondary side dimmer.

**Certification:**

- CETL listed and approved.
- FCC Certified (won't interfere with electronics)

