

MTT-300SS

Low voltage Transformer

| MODEL NUMBER | POWER RATING | PRIMARY VOLTAGE | SECONDARY VOLTAGE |
|--------------|--------------|-----------------|-------------------|
| MTT-300SS | 300W | 120V | 12-15V |

SPECIFICATIONS:

Housing Material:

- 304 Brushed Stainless Steel

Core:

- Fully encapsulated Toroidal core

Features:

- Sealed hinged door removable and lockable, pre-scored knockouts sides and bottom panel, toolless removeable bottom panel, timer receptacle inside, photocell ready bypass loop, two commons per circuit, primary thermal protection included, secondary side magnetic circuit breaker included, oversized terminal blocks multiple wire input. Most components field replaceable. Operates cooler, quieter and more efficient than Magnetic core transformers.

Dimensions:

- 6.5"W x 16.5"H x 6"D

Watts:

- 300

Wiring:

- 125° C rated internal wiring.

Electrical specs:

- 12-15-volt range terminal blocks, 300 watts. 6'-heavy duty power cord 120-volt input, surge suppressor included – prevents initial start overload, 115 AMP terminal block included.

Mounting/ Fasteners:

- Keyhole slot quick mount bracket.

Certification:

- CETL listed and approved.

