



LVC-PAR36

LED - LVC-PAR36

MATERIAL	MODEL NUMBER	LUMENS	KELVIN
Thermal Plastic Body	LVC4-PAR36-FL-27K	400 Lumens	2200K
Thermal Plastic Body	LVC4-PAR36-WF-27K	400 Lumens	2700K
Thermal Plastic Body	LVC6-PAR36-FL-27K	600 Lumens	2700K
Thermal Plastic Body	LVC6-PAR36-WF-27K	600 Lumens	2700K
Thermal Plastic Body	LVC8-PAR36-FL-27K	800 Lumens	2700K
Thermal Plastic Body	LVC8-PAR36-WF-27K	800 Lumens	2700K
Thermal Plastic Body	LVC4-PAR36-FL-30K	400 Lumens	3000K
Thermal Plastic Body	LVC4-PAR36-WF-30K	400 Lumens	3000K
Thermal Plastic Body	LVC6-PAR36-FL-30K	600 Lumens	3000K
Thermal Plastic Body	LVC6-PAR36-WF-30K	600 Lumens	3000K
Thermal Plastic Body	LVC8-PAR36-FL-30K	800 Lumens	3000K
Thermal Plastic Body	LVC8-PAR36-WF-30K	800 Lumens	3000K

SPECIFICATIONS:

Material:

- Thermal plastic body

Socket Type:

- Par 36 terminal screw base

Dimensions:

- LXC Series: 2" W x 1.5" H

Voltage Range:

- 9-15 volts AC/DC

IP Rating:

- IP 67
- Made for use in enclosed fixtures

Electrical:

- LVC4-PAR36: 400 Lumens, 5.5 Watts, .67 VA, .7 PF
- LVC6-PAR36: 600 Lumens, 7.5 Watts, .83 VA, .7 PF
- LVC8-PAR36: 800 Lumens, 11 Watts, 1.05 VA, .7 PF

Rated Hours:

- 35,000

Dimmable:

- Yes with Lutron magnetic dimmers

Certification:

- CETL listed and approved.
- FCC Certified (won't interfere with electronics)

