



## LV1-T5, LV2-T5, LV2-S8

### LED - Wedge

MATERIAL	MODEL NUMBER	LUMENS	KELVIN
UV protected Clear Silica	LV1-T5-27K LED	120 Lumens	2700K
UV protected Clear Silica	LV1-T5-30K LED	120 Lumens	3000K
UV protected Clear Silica	LV2-T5-27K LED	170 Lumens	2700K
UV protected Clear Silica	LV2-T5-30K LED	170 Lumens	3000K
UV protected Clear Silica	LV2-S8WDG-27K LED	170 Lumens	2700K
UV protected Clear Silica	LV2-S8WDG-30K LED	170 Lumens	3000K

### SPECIFICATIONS:

**Material:**

- Solid Silica Gel

**Finish:**

- Clear, UV inhibitor infused to prevent yellowing or caking.

**Socket Type:**

- T5 Wedge base or S8 Wedge base

**Pin gap width:**

- T5: 5.5 Millimeters
- S8: 12.6 Millimeters

**Dimensions:**

- LV1-T5WDG: .5" W x 1.2" H
- LV2-T5WDG: .5" W x 1.2" H
- LV2-S8WDG: .9" W x 1.7" H

**Voltage Range:**

- 12-15 volts AC/DC

**IP Rating:**

- IP 65
- Made for use in enclosed fixtures.

**Electrical:**

- LV1-T5WDG: 120 Lumens, 1.5 Watts, .13 VA, .7 PF
- LV2-T5WDG: 170 Lumens, 2.5 Watts, .17 VA, .7 PF
- LV2-S8WDG: 170 Lumens, 2.5 Watts, .17 VA, .7 PF

**Rated Hours:**

- 25,000

**Dimmable:**

- Yes with secondary side dimmer.

**Certification:**

- CETL listed and approved.
- FCC Certified (won't interfere with electronics)

