



## ZCT-300SS

### Low voltage Transformer

MODEL NUMBER	POWER RATING	PRIMARY VOLTAGE	SECONDARY VOLTAGE
ZCT-300SS	300W	120V	12V

## SPECIFICATIONS:

#### Housing Material:

- 304 Brushed Stainless Steel

#### Core:

- Fully encapsulated EI magnetic core.

#### Features:

- Wifi enabled app smart transformer. Schedule up to four zones of: Independent timing, Grouped timing, On demand timing
- App enables naming of zones
- Access via home router and smart device app: iOS and Android app-based control, Daylight savings time option, Multiple device control of one transformer, Control up to four transformers from one device
- Included 100' range extender wifi antennae
- 304 brushed stainless steel - case and inside panel
- Quick mount bracket
- Sealed removable lockable hinged door
- Pre-scored knockouts on side and bottom panel
- Tool-less removable bottom panel
- Two commons per circuit
- Includes primary thermal protection
- Includes secondary side magnetic circuit breaker
- Oversize terminal blocks

#### Dimensions:

- 5.75"W x 10.5"H x 4.75"D

#### Watts:

- 300

#### Wiring:

- 125° C rated internal wiring.

#### Electrical specs:

- 12-volt range terminal blocks, 300 watts. 6' –heavy duty power cord 120-volt input, surge suppressor included – prevents initial start overload, 115 AMP terminal block included.

#### Mounting/ Fasteners:

- Keyhole slot quick mount bracket.
- Note: 2.4 Ghz Wifi signal required.

#### Certification:

- CETL listed and approved.