

AF

Area Floods



Area Flood

AF2900WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant flat clear and frosted glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy field adjustment
- Double O-ring seal for added moisture protection
- Weather resistant aged finish - Brass
- (WB) Weathered Brass - AF2900WB
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - T3 35 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LV1-T3
- LV2-T3
- LV3-T3

DIMENSIONS

- 5" L x 4.375" W x 2" H across the front shroud



AF2900WB



LV1-T3



LV2-T3



LV3-T3

Area Flood

AF2900WB-LV2T3

KITTED FIXTURE

PRODUCT DESCRIPTION

- The AF2900WB-LV2T3 includes:
 - AF2900WB cast brass WB small area flood
 - (GS1) ABS ground stake
 - LV2-T3-27K lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED Lamp - 5 year warranty

LED LAMP INCLUDED

- LV2-T3-27K
- 9-15 V AC/DC
- T3 BI pin lamp
- IP67 rated
- Silica gel filled
- 35 x 35 SMD chipset
- 2700K
- 180 Lumens
- C ETL listed and approved
- FCC certified

DIMENSIONS

- 5" L x 4.375" W x 2" H across the front shroud



AF2900WB



LV2-T3

Area Flood

AF1300BK/BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Optional cowling thumb set screw - allowing downlight use
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DS1300BK
 - (BZ) Bronze - DS1300BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps
- LV1-T3
- LV2-T3
- LV3-T3

DIMENSIONS

- 6.25" L x 2.5" W across the front shroud



AF1300BK



AF1300BZ



LV1-T3



LV2-T3



LV3-T3



LXC2-MR16



LXC3-MR16



LXC5-MR16

Area Flood

AF1300BK/BZ-LV2T3

KITTED FIXTURE

PRODUCT DESCRIPTION

- The AF1300BK-LV2T3 and AF1300BZ-LV2T3 include:
 - Cast aluminum powder coated large area flood
 - (GS1) ABS ground stake
 - LV2-T3-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty
- LED lamp - 5 year warranty

LED LAMP INCLUDED

- LV2-T3-27K
- 9-15 V AC/DC
- T3 BI pin lamp
- IP67 rated
- Silica gel filled
- 35 x 35 SMD chipset
- 2700K
- 180 Lumens
- C ETL listed and approved
- FCC certified

DIMENSIONS

- 6.25" L x 2.5" W across the front shroud



AF1300BK



AF1300BZ



LV2-T3

Area Flood

AF1300BK/BZ-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The AF1300BK-LXC2 and AF1300BZ-LXC2 include:
 - Cast aluminum powder coated large area flood
 - (GS1) ABS ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 6.25" L x 2.5" W across the front shroud



AF1300BK



AF1300BZ



LXC2-MR16

Area Flood

AF2300WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant flat clear and frosted glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O-ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - two options:
 - MR16 50 W Max
 - T3 35 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps
- LV1-T3
- LV2-T3
- LV3-T3

DIMENSIONS

- 6.75 L x 4" W x 3" H across the front shroud



AF2300WB



LV1-T3



LV2-T3



LV3-T3



LXC2-MR16



LXC3-MR16



LXC5-MR16

Area Flood

AF2300WB-LV2T3

KITTED FIXTURE

PRODUCT DESCRIPTION

- The AF2300WB-LV2T3 includes:
 - AF2300WB cast brass WB large area flood
 - (GS1) ABS ground stake
 - LV2-T3-27K lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 5 year warranty

LED LAMP INCLUDED

- LV2-T3-27K
- 9-15 V AC/DC
- T3 BI pin lamp
- IP67 rated
- Silica gel filled
- 35 x 35 SMD chipset
- 2700K
- 180 Lumens
- C ETL listed and approved
- FCC certified

DIMENSIONS

- 6.75 L x 4" W x 3" H across the front shroud



AF2300WB



LV2-T3

Area Flood

AF2300WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The AF2300WB-LXC2 includes:
 - AF2300WB cast brass WB large area flood
 - (GS1) ABS ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 6.75 L x 4" W x 3" H across the front shroud



AF2300WB



LXC2-MR16

Integrated LED Mini Flood

ILED-AF4407BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Includes (GS-mini) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- 270° adjustable rotating mount
- Weather resistant powder coat finish - aluminum
 - (BZ) Bronze - AF4407BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- Input 9-15 volts
- 10' - #18/2 direct bury landscape lighting wire
- Integrated LED's - no lamp required
- LED diodes have 90° beam spread
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC certified

LED - LIGHTING MODULE

- Integrated LED - no lamp required
- 100 Lumens, 1.25 Watts, 2 VA, .62 PF
- 2700K Kelvin temperature

DIMENSIONS

- LED light bar - 7" W x .75" H x .5" D
- Post - 5.75" H x .33" W
- Mini ground stake - 7" H x 1" W (GS-mini)



ILED-AF4407BZ