

DS

Directional Spots



3D page



Directional Spot

DS1300BK/BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Optional cowling thumb set screw - allowing downlight use
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DS1300BK
 - (BZ) Bronze - DS1300BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2
- LXC3
- LXC5

DIMENSIONS

- 6.25" L x 2.5" W



DS1300BK



DS1300BZ



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS1300BK/BZ-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS1300BK-LXC2 and DS1300BZ-LXC2 include:
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DS1300BK
 - (BZ) Bronze - DS1300BZ
 - GS1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 6.25" L x 2.5" W



DS1300BK



DS1300BZ



LXC2-MR16



Directional Spot

DS2100WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2
- LXC3
- LXC5

DIMENSIONS

- 5.25" L x 2.125" W



DS2100WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2100WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2100WB-LXC2 includes:
 - DS2100WB cast brass WB finish spotlight
 - G5-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700k
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.125" W



DS2100WB



LXC2-MR16

Directional Spot

DS2300WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2
- LXC3
- LXC5

DIMENSIONS

- 5.25" L x 2.5" W



2300WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2300WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2300WB-LXC2 includes:
 - DS2300WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 Year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.5" W



DS2300WB



LXC2-MR16

Directional Spot

DS2600WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Adjustable / removable cowling for discrete lighting
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2
- LXC3
- LXC5

DIMENSIONS

- 5.25" L x 2.5" W



DS2600WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2600WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2600WB-LXC2 includes:
 - DS2600WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.5" W



DS2600WB



LXC2-MR16

Directional Spot

DS2800WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2
- LXC3
- LXC5

DIMENSIONS

- 7.25" L x 2.5" W



DS2800WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2800WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2800WB-LXC2 includes:
 - DS2800WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology
- 7 year warranty

DIMENSIONS

- 7.25" L x 2.5" W



DS2800WB



LXC2-MR16

Directional Spot

DS2905WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Adjustable / removable cowling for discrete lighting
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required
- DS2905WB - MR11 35 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LX2-MR11-27K

DIMENSIONS

- 4.25" L x 1.625" W



DS2905WB



LX2-MR11

Directional Spot

DS2905WB-LX2MR11

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2905WB-LX2MR11 includes:
 - Cast brass WB finish spotlight
 - GS1 ground stake
 - LX2-MR11-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 5 year warranty

LED LAMP INCLUDED

- LX2-MR11-27K
- 9 - 15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 240 Lumens
- COB technology

DIMENSIONS

- 4.25" L x 1.625" W



DS2905WB



LX2-MR11

Directional Spot

DS2336WB

MATERIAL / FEATURES

- Solid brass fixture housing
- Cast brass knuckle assembly
- Open faced no lens fixture
- Includes (GS1) ABS ground stake, ½" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy adjustments
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire with terminal spade connectors
- Lamp required - PAR36 75 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LVC4-PAR36
- LVC6-PAR36
- LVC8-PAR36

DIMENSIONS

- 4.53" W x 3.15" D x 9.25" L (from thread to tip of cowling)



DS2336WB



LVC4-PAR36



LVC6-PAR36



LVC8-PAR36

Integrated LED Directional Spot

ILED-DS2025WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Heat resistant glass lens
- Watertight sealed wire ingress grommet
- Brass Phillips head thumb screws on bracket for easy field adjustment
- Watertight sealed gasket
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Includes GS-mini ABS ground stake
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 25' submersible rated lighting wire lead
- Integrated LED - no lamp required
- Heat sinks for long life
- Low voltage transformer required (not included)
- C ETL listed and approved

LED - LIGHTING MODULE

- Integrated LED - no lamp required
- 282 Lumens , 3 W, 3.96 VA, .75 PF
- 2700 Kelvin temperature
- Beam spread - 70 degrees

DIMENSIONS

- 2" D x 2.75" W x 2.5" H



ILED-DS2025WB



Hybrid Integrated Directional Spot

HI-DS1560BK/BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Adjustable cowling
- Heat resistant angled glass lens
- Includes (GS1) ABS ground stake, ½" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O-ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - HI-DS1560BK
 - (BZ) Bronze - HI-DS1150BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- Includes HI-LEDMR16-600 LED lighting module
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC certified

LED - LIGHTING MODULE

- Encapsulated thermal plastic LED module
- COB chipset technology
- Heat sink for better thermal management
- Three pre-set button guided Lumen outputs
 - 300, 400, 600 Lumens
- Three pre-set lighting module beam spread options
 - 15, 38, 60 degrees
- 300 Lumens
 - 3W, 4.06 VA, .77 PF
- 400 Lumens
 - 5W, 6.44 VA, .77 PF
- 600 Lumens
 - 7W, 9.00 VA, .77 PF
- Field replaceable LED module
 - HI-LEDMR16-600
- IP65
- 2700K, 90 CRI

DIMENSIONS

- 5.30"L x 2.58"W



HI-DS1560BK



HI-DS1560BZ



Hybrid Integrated Directional Spot

HI-DS2560WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Heat resistant angled glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED module - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- Includes HI-LEDMR16-600 LED lighting module
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC certified

LED - LIGHTING MODULE

- Encapsulated thermal plastic LED module
- COB chipset technology
- Heat sink for better thermal management
- Three pre-set button guided Lumen outputs
 - 300, 400, 600 Lumens
- Three pre-set lighting module beam spread options
 - 15, 38, 60 degrees
- 300 Lumens
 - 3W, 4.06 VA, .77 PF
- 400 Lumens
 - 5W, 6.44 VA, .77 PF
- 600 Lumens
 - 7W, 9.00 VA, .77 PF
- Field replaceable LED module
 - HI-LEDMR16-600
- IP65
- 2700K, 90 CRI

DIMENSIONS

- 5.30"L x 2.58"W



HI-DS2560WB

