

Hybrid Integrated Directional Spot

HI-DS1560BK/BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Adjustable cowling
- Heat resistant angled glass lens
- Includes (GS1) ABS ground stake, ½" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O-ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - HI-DS1560BK
 - (BZ) Bronze - HI-DS1560BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- Includes HI-LEDMR16-600 LED lighting module
- Low voltage transformer required (not included)
- CETL listed and approved
- FCC certified

LED - LIGHTING MODULE

- Encapsulated thermal plastic LED module
- COB chipset technology
- Heat sink for better thermal management
- Three pre-set button guided Lumen outputs
 - 300, 400, 600 Lumens
- Three pre-set lighting module beam spread options
 - 15, 38, 60 degrees
- 300 Lumens
 - 3W, 4.06 VA, .77 PF
- 400 Lumens
 - 5W, 6.44 VA, .77 PF
- 600 Lumens
 - 7W, 9.00 VA, .77 PF
- Field replaceable LED module
 - HI-LEDMR16-600
- IP65
- 2700K, 90 CRI

DIMENSIONS

- 5.30"L x 2.58"W



HI-DS1560BK



HI-DS1560BZ

