

Integrated LED Contemporary Path

ILED-PL2500WB

MATERIAL / FEATURES

- Integrated LED adjustable lighting fixture
 - Multiple applications include path lighting, area lighting, flood lighting, sconce lighting
- Heat sink for maximum heat dissipation and life span
- Thermal frosted lens to optimize event distribution of light
- Adjustable LED head rotates 270 degrees
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Post: 1" x 1" x 22" H
- Shade: 5" x 5" x .75"
- (GS3) ABS ground stake
- Fixture - 10 year warranty

ELECTRICAL

- 12 Volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC certified

LED - LIGHTING MODULE

- LED module is encapsulated behind thermal plastic frosted lens
- COB chipset technology
- Heat sink for better thermal management
- 380 Lumen high output
- 140 degree beam spread
- 2700K
- 3.15W, 3.96 VA, .75 PF



Intertek



ILED-PL2500WB