

ECO100PC

MATERIAL / FEATURES

- Commercial grade ABS plastic
- Quick mount bracket
- Includes field replaceable timer module
- Countdown timer function
- 1, 2, 4, 6, 8 hour durations
 - Always OFF
 - Always ON
- Includes low voltage photocell
- Includes secondary side magnetic circuit breaker
- 2 year warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Terminals for output
- Fully encapsulated El magnetic core
 - 125° C rated internal wiring
- Wire connectors required (not included)
- Low voltage landscape lighting fixtures required (not included)
- Low voltage landscape lighting lamps required (not included)
- C ETL listed and approved

MODELS

• ECO100PC - 100 Watts

DIMENSIONS

• 4"W x 6"H x 3"D









TM-ECO-TM

www.unvls.com | sales@unvls.com | P: (888) 866-4765 | F: (888) 806-5557 **107**

ECO120, 200, 300

MATERIAL / FEATURES

- 304 brushed stainless steel
- Quick mount bracket
- Includes field replaceable timer module
- Countdown timer function
 - 1, 2, 4, 6, 8 hour durations
 - Always OFF
 - Always ON
- Includes low voltage photocell
- Includes secondary side magnetic circuit breaker
- 2 year warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Terminals for output
- Fully encapsulated El magnetic core
 - 125° C rated internal wiring
- Wire connectors required (not included)
- Low voltage landscape lighting fixtures required (not included)
- Low voltage landscape lighting lamps required (not included)
- C ETL listed and approved

MODELS

- ECO120SS 120 Watts
- ECO200SS 200 Watts
- ECO300SS 300 Watts

DIMENSIONS

• 5"W x 8"H x 4"D









TP-ECO-TM

www.unvls.com | sales@unvls.com | P: (888) 866-4765 | F: (888) 806-5557

MTM SERIES

MATERIAL / FEATURES

- 304 brushed stainless steel case and inside panel
- Quick mount bracket
- Sealed removable lockable hinged door
- Pre-scored knockouts sides and bottom panel
- Tool less removable bottom panel
- Timer receptacle
- Photocell ready bypass loopTwo commons per circuit
- Includes primary thermal protection
- Includes secondary side magnetic circuit breaker
 Oversize terminal blocks
- Lifetime warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Includes surge suppressor prevents initial start overload
 Includes 115 amp terminal block
- Fully encapsulated ei magnetic core
 - Óperates whisper quiet
 - Caution may be very hot do not touch when its on
 - 125° c rated internal wiring
 - 12-15 volt terminal range
- Wire connectors required (not included)
- Low voltage landscape lighting fixtures required (not included)
- Low voltage landscape lighting lamps required (not included)
- C ETL listed and approved

MODELS

- MTM150SS 150 Watts
- MTM200SS 200 Watts
- MTM300SS 300 Watts

DIMENSIONS

- MTM150/200 5.75"W x 10.5"H x 4.75"D
- MTM300SS 6.5" W x 16.5" H x 6" D



MTM300SS







MTM0300SS

MTT SERIES

MATERIAL / FEATURES

- 304 brushed stainless steel case and inside panel
- Quick mount bracket
- Sealed removable lockable hinged door
- Pre-scored knockouts sides and bottom panel
- Tool less removable bottom panel
- Timer receptacle
- Photocell ready bypass loopTwo commons per circuit
- Includes primary thermal protection
- Includes secondary side magnetic circuit breaker
 Oversize terminal blocks
- Lifetime warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Includes surge suppressor prevents initial start overload
 Includes 115 amp terminal block
- Fully encapsulated Toroidal core
 - Óperates whisper quiet
 - Cool to the touch
 - 125° C rated internal wiring
 - 12-15 volt terminal range
- Wire connectors required (not included)
 Low voltage landscape lighting fixtures required (not included)
- Low voltage landscape lighting lamps required (not included)
- C ETL listed and approved

MODELS

- MTT050SS 50 Watts
- MTT100SS 100 Watts
- MTT150SS 150 Watts
- MTT300SS 300 Watts
- MTT600SS 600 Watts

DIMENSIONS

- MTT050, 100, 150 5.75"W x 10.5"H x 4.75"D
- MTT300, MTT600 6.5"W x 16.5"H x 6"D



MTT600SS







MTT600SS

MTP SERIES

MATERIAL / FEATURES

- 304 brushed stainless steel case and inside panel
- Quick mount bracket
- Sealed removable lockable hinged door
- Pre-scored knockouts sides and bottom panel
- Tool less removable bottom panel
- Timer receptacle
- Photocell ready bypass loopTwo commons per circuit
- Includes primary thermal protection
- Includes secondary side magnetic circuit breaker
 Oversize terminal blocks
- Lifetime warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Includes surge suppressor prevents initial start overload
 Includes 115 amp terminal block
- Fully encapsulated Toroidal core
 - Óperates whisper quiet
 - Cool to the touch
 - 125° C rated internal wiring
 - 12-22 volt taps Wire connectors required (not included)
- Low voltage landscape lighting fixtures required (not included)
- Low voltage landscape lighting lamps required (not included)
- C ETL listed and approved

MODELS

- MTP600SS 600 Watts
- MTP900SS 900 Watts
- MTP1200SS 1200 Watts

DIMENSIONS

- MTP600 6.5"W x 16.5"H x 6"D
- MTP900,1200 8.5"W x 17.5"H x 7"D



MTP300SS







MTP300SS

UTR SERIES

MATERIAL / FEATURES

- 304 brushed stainless steel case and inside panel
- Quick mount bracket
- Sealed removable lockable hinged door
- Pre-punched knockouts with plastic inserts side and bottom panel
 Tool less removable bottom panel
 Removable project note card
 (2) 12" x 1.25" PVC conduits
- - (1) 1.25" coupling
 (1) Includes 1.25" male adapter
- Timer receptacle
 Photocell ready bypass loop

- Priotocell ready bypass loop
 Two commons per circuit
 Includes primary thermal protection
 Includes secondary side magnetic circuit breaker
 Oversize terminal blocks
 Lifetime warranty

ELECTRICAL

- Low voltage landscape lighting transformer
- 6' heavy duty power cord
- Includes surge suppressor prevents initial start overload
 Includes 115 amp terminal block
 Fully encapsulated Toroidal core

- Fully encapsulated Toroidal core

 Operates whisper quiet
 Cool to the touch

 125° C rated internal wiring
 12-15 Volt terminal range
 Wire connectors required (not included)
 Low voltage landscape lighting fixtures required (not included)
 Low voltage landscape lighting lamps required (not included)
 C ETL listed and approved
 Ill approved for hard wire applications

- UL approved for hard wire applications

MODELS

- UTR100SS 100 Watts
- UTR300SS 300 Watts

DIMENSIONS

- UTR100SS 7"W x 13"H x 6.5"D
- UTR300SS 7"W x 13"H x 6.5"D



UTR100SS





ZCT SERIES

MATERIAL / FEATURES

- Wifi enabled app smart transformer
 Schedule up to four zones of
- Independent timing
 Grouped timing
 On demand timing
 App enables naming of zones
- Access via home router and smart device app
 iOS and Android app-based control
- Daylight savings time option
 Multiple device control of one transformer
 Control up to four transformers from one device
 Included 100' range extender wifi antennae
 304 brushed stainless steel case and inside panel
 Quick mount bracket

- Quick mount bracket
 Sealed removable lockable hinged door
 Pre-scored knockouts on side and bottom panel
 Tool-less removable bottom panel
 Two commons per circuit
 Includes primary thermal protection
 Includes secondary side magnetic circuit breaker
 Oversize terminal blocks
 5 year warranty

ELECTRICAL

- Low voltage landscape lighting transformer6' Heavy duty power cord
- Includes surge suppressor prevents initial start overload
 Includes 115 amp terminal block
 Fully encapsulated Toroidal core

- Operates whisper quiet
 Cool to the touch
 125° C rated internal wiring
- 12-volt output
- Wire connectors required (not included)
- Low voltage landscape lighting fixtures required (not included)
 Low voltage landscape lighting lamps required (not included)
 C ETL listed and approved

- Compatible with 2.4Ghz wireless routers only

MODELS

- ZCT150SS 150 WattsZCT200SS 200 Watts
- ZCT300SS 300 Watts

DIMENSIONS

• 5.75"W x 10.5"H X 4.75"D



TOOL-LESS DROP-DOWN PANEL







Transformer Accessories

12 VOLT DIMMER

MATERIAL / FEATURES

- Low voltage Dimmer for low voltage transformers
- Aluminum face plate
- Polycarbonate plastic watertight housing
- Includes
 - (4) Stainless steel anchor screws
 - (1) extra fuse stat
 - (4) wire connectors
- Watertight grommet
- Rubber gasket

ELECTRICAL

- 120-Watt total capacity
- Operating range 12 VAC
- 10 Amps
- IP 67
- Trim pot adjustment screw

MODEL

• DM1120-BK

DIMENSIONS

• 2.75"W X 4.5"H x 3.6"D









Transformer Accessories

MT1 - MECHANICAL TIMER

- Up to 48 ON/OFF settings
- 24-hour cycle
- Captive pins never get lost
- Cycle repeats daily
- Manual on/off override
- Fits into MTM, MTT, MTP and UTR transformers
- 90 day warranty

AT-DT620CL - ASTRONOMICAL DIGITAL TIMER

- 7-day astronomical timer
- Fits into MTM, MTT, MTP and UTR transformers
- Fixture 90 day warranty

DT - DIGITAL TIMER

- 7-day programmable timer
- LCD Screen
- Battery back up
- Fits into MTM, MTT, MTP and UTR transformers
- Fixture 90 day warranty

PC - 120-VOLT PHOTOCELL

- Plug in photocell
- Use by itself to stay on dusk to dawn
- Use with MT1 or DT to set off time
- Fits into MTM, MTT, MTP and UTR transformers
- Fixture 90 day warranty





MT AT-DT620CL



DT







PC

www.unvls.com | sales@unvls.com | P: (888) 866-4765 | F: (888) 806-5557