

LED - LV BI Pin Series

LV1-T3, LV2-T3, LV3-T3

SPECIFICATIONS

- Silica gel lamps
- G4 socket base
- 80+ CRI
- 25,000 hour rated
- UV infused inhibitors
- LED's are measured and tested at 12 Volts
 - Longest life occurs at 12 Volts
- Stainless steel pins
- Silver soldering for long lasting performance
- Made for use in enclosed fixtures and damp location
- 2200K, 2700K and 3000K color temperature
- LV1-T3
 - 120 Lumens, 1.5 Watts, .13 VA, .7 PF
- LV2-T3
 - 180 Lumens, 2.5 Watts, .17 VA, .7 PF
- LV3-T3
 - 260 Lumens, 3.5 Watts, .21 VA, .7 PF
- IP Rating 65
- Lamp - 5 year warranty

ELECTRICAL

- 9-15 V AC/DC
- Constant current driver for long life
- Dimmable with Lutron magnetic dimmers
 - Dimming may reduce life span
- Enclosed fixture required (not included)
- Low voltage transformer or electronic transformer required (not included)
- C ETL listed and approved
- FCC certified

MODELS

- LV1-T3-27K or LV1-T3-30K
- LV2-T3-22K, LV2-T3-27K, or LV2-T3-30K
- LV3-T3-22K, LV3-T3-27K, or LV3-T3-30K

DIMENSIONS


- LV1 - .35" W x 1" H
- LV2 - .5" W x 1.10" H
- LV3 - .6" W x 1.25" H



LV1-T3



LV2-T3



LV3-T3

