



LV1-T3, LV2-T3, LV3-T3

LED - Bi Pin

MATERIAL	MODEL NUMBER	LUMENS	KELVIN
UV protected Clear Silica	LV2-T3-22K LED	180 Lumens	2200K
UV protected Clear Silica	LV3-T3-22K LED	260 Lumens	2200K
UV protected Clear Silica	LV1-T3-27K LED	120 Lumens	2700K
UV protected Clear Silica	LV2-T3-27K LED	180 Lumens	2700K
UV protected Clear Silica	LV3-T3-27K LED	260 Lumens	2700K
UV protected Clear Silica	LV1-T3-30K LED	120 Lumens	3000K
UV protected Clear Silica	LV2-T3-30K LED	180 Lumens	3000K
UV protected Clear Silica	LV3-T3-30K LED	260 Lumens	3000K

SPECIFICATIONS:

Material:

- Solid Silica Gel

Finish:

- Clear, UV inhibitor infused to prevent yellowing or caking.

Socket Type:

- G4 Bi Pin base.

Pin gap width:

- 4 Millimeters

Dimensions:

- LV1: .35" W x 1" H
- LV2: .5" W x 1.10" H
- LV3: .6" W x 1.25" H

Voltage Range:

- 12-15 volts AC/DC

IP Rating:

- IP 65
- Made for use in enclosed fixtures.

Electrical:

- LV1-T3: 120 Lumens, 1.5 Watts, .13 VA, .7 PF
- LV2-T3: 180 Lumens, 2.5 Watts, .17 VA, .7 PF
- LV3-T3: 260 Lumens, 3.5 Watts, .21 VA, .7 PF

Rated Hours:

- 25,000

Dimmable:

- Yes with secondary side dimmer.

Certification:

- CETL listed and approved.
- FCC Certified (won't interfere with electronics)

