

LED - LVC MR16

LVC MR16

SPECIFICATIONS

- Thermal plastic body 3 and 5 watts
- Aluminum body 7 watt
- Epoxy potted circuitry
- GU5.3 base socket
- 80+ CRI
- 15,000 Hour rated
- Multiple beam spreads
- (FL) Flood 40°
- (WFL) Wide flood 60°
- Stainless steel pins
- Made for use in enclosed fixtures and damp location
- 2700K & 3000K Color
- LVC2-MR16-27K
 - 240 Lumens, 3 Watts, .39 VA, .7 PF
- LVC3-MR16-27K
 - 350 Lumens, 5 Watts, .60 VA, .7 PF
- LVC5-MR16-27K
 - 450 Lumens, 7 Watts, .72 VA, .7 PF
- IP Rating 54

ELECTRICAL

- 9-15 V AC/DC
- Constant current driver for long life
- Dimmable with Lutron magnetic dimmers
 - Dimming may reduce life span
- Enclosed fixture required (Not Included)
- Low voltage transformer or electronic transformer
- C ETL Listed and approved
- FCC Certified

MODELS

- LVC2-MR16-FL-27K
- LVC2-MR16-FL-30K
- LVC2-MR16-WF-27K
- LVC3-MR16-FL-27K
- LVC3-MR16-FL-30K
- LVC3-MR16-WF-27K
- LVC5-MR16-FL-27K
- LVC5-MR16-WF-27K

DIMENSIONS

- LVC Series 2" W x 1.625" H



LVC2-MR16



LVC3-MR16



LVC5-MR16

