

# Ledge Light

## LL44 SERIES

### MATERIAL / FEATURES

- Stainless steel
  - Mounting bracket, screws, glare shield
- Cast aluminum - light bar
- Weather resistant powder coat finish - aluminum
  - (BK) Black
  - (BZ) Bronze
  - (GY) Gray
- Mounting bracket includes pre-scored corners for retrofit installations
  - Can be used with or without mounting bracket
- Glare shield included – removable
- LED light bar can be used without mounting bracket or glare shield
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10-year warranty

### ELECTRICAL

- Input 9-15 volts
- 10' - #18/2 direct bury landscape lighting wire
- No lamp required
- LED diodes have 90° beam spread
- Low voltage transformer required (not included)
- Includes wire connectors
- C ETL listed and approved
- FCC certified

### LED - LIGHTING MODULE

- LED integrated - no lamp required
- LL4403 - 25 lumens, .4 Watts, VA .60, .36 PF
- LL4407 - 100 lumens, 1.5 Watts, VA 2, .62 PF
- LL4413 - 200 lumens, 2.2 Watts, VA 3.3, .85 PF
- Kelvin temperature 2700K & 3000K

### DIMENSIONS

- LL4403 - 3"W x .75"H x 3"D
- LL4407 - 7"W x .75"H x 3"D
- LL4413 - 13"W x .75"H x 3"D



LL4403BZ



LL4407GY



LL4413BZ